

Сечение провода, мм <sup>2</sup> *	Диаметр под винт	Размер, мм						Упаковка, шт.	Код	Изоляторы для наконечников	
		С	В	Л	А	М	Н			Код	Упаковка, шт.
95/70	8	13	23	47	19,5	9	8	50	2I8F	2PI	100
	10	13	23	52	19,5	11	10	50	2I10F		
	12	13	23	55	19,5	13	12	50	2I12F		
	14	13	25	60	19,5	15	14	50	2I14F		
95	6	13	26	51	20	8	7	25	2L6	2PL	100
	8	13,5	26	55	20	9	8	25	2L8		
	10	13,5	26	58	20	11	10	25	2L10		
	12	13,5	26	62	20	13	12	25	2L12		
	14	13,5	26	65	20	15	14	25	2L14		
	16	13,5	26	67	20	17	16	25	2L16		
	18	13,5	32	71	20	19	18	25	2L18		
	20	13,5	32	77	20	21	20	25	2L21		
120/95	8	15	27	54	22	9	8	25	2L8F	2PL	100
	10	15	27	58	22	11	10	25	2L10F		
	12	15	27	59	22	13	12	25	2I12F		
	14	15	27	66	22	15	14	25	2L14F		
120	8	15,2	29	53	22,5	9	8	25	2M8	2PM	50
	10	15,2	29	60	22,5	11	10	25	2M10		
	12	15,2	29	64	22,5	13	12	25	2M12		
	14	15,2	29	65	22,5	15	14	25	2M14		
	16	15,2	29	68	22,5	17	16	25	2M16		
	18	15,2	29	76	22,5	19	18	25	2M18		
	20	15,2	29	80	22,5	22	20	25	2M21		
	22	15,2	29	86	22,5	25	23	25	2M22		
150/120	10	16,5	30	61	25	11	10	25	2M10F	2PM	50
	12	16,5	30	65	25	13	12	25	2M12F		
	14	16,5	30	69	25	15	14	25	2M14F		
	16	16,5	30	72	25	17	16	25	2M16F		
150	8	16,5	32	59	25	10	8	20	2N8	2PN	50
	10	16,5	32	62	25	11	10	20	2N10		
	12	16,5	32	66	25	13	12	20	2N12		
	14	16,5	32	70	25	15	14	20	2N14		
	16	16,5	32	74	25	17	16	20	2N16		
	18	16,5	32	78	25	19	18	20	2N18		
185	10	19,2	36	68	28	11	10	10	2O10	2PO	50
	12	19,2	36	72	28	13	12	10	2O12		
	14	19,2	36	76	28	15	14	10	2O14		
	16	19,2	36	79	28	17	16	10	2O16		
	18	19,2	36	83	28	19	18	10	2O18		
	20	19,2	36	89	28	22	20	10	2O21		
240	10	21,5	39	74	32	11	10	10	2P10	2PP	25
	12	21,5	39	78	32	13	12	10	2P12		
	14	21,5	39	82	32	15	14	10	2P14		
	16	21,5	39	85	32	17	16	10	2P16		
	18	21,5	39	90	32	19	18	10	2P18		
300	12	23,7	44	85	36	14	12	10	2Q12	2PQ	25
	14	23,7	44	89	36	16	14	10	2Q14		
	16	23,7	44	93	36	18	16	10	2Q16		
	18	23,7	44	98	36	21	18	10	2Q18		
	20	23,7	44	102	36	23	20	10	2Q21		
400	16	27	51	101	40	18	16	5	2R16	2PR	25
	18	27	51	104	40	21	18	5	2R18		
	20	27	51	110	40	24	21	5	2R21		
500	16	30,3	57	119	49	23	16	5	2S16	2PS	20
	20	30,3	57	123	49	24	20	5	2S21		
630	16	33	62	133	60	23	16	5	2T16	2PT	20
	20	33	62	138	60	24	20	5	2T21		
800	20	38	72	154	65	26	20	5	2U21	-	-
1000	20	44	80	162	70	26	20	5	2V21	-	-

\* Сечение провода для 1–3 класса гибкости